



[www.chinatag.com](http://www.chinatag.com)

**CHINATAG**

640-901

Building Scalable Cisco  
Internetworks (BSCI)

Study Guide  
DEMO Version

Copyright (c) 2003 Chinatag LLC. All rights reserved.

## **Important Note Please Read Carefully**

For demonstration purpose only, this free version Chinatag study guide contains **10** full length questions selected from our full version products which have more than **200** questions each.

This Study guide has been carefully written and compiled by Chinatag certification experts. It is designed to help you learn the concepts behind the questions rather than be a strict memorization tool. Repeated readings will increase your comprehension.

For promotion purposes, all PDF files are **not** encrypted. Feel free to distribute copies among your friends and let them know Chinatag website. Our IT certification products start at only **\$7.99**.

## **Study Tips**

This product will provide you questions and answers along with detailed explanations carefully compiled and written by our experts. Try to understand the concepts behind the questions instead of cramming the questions. Go through the entire document at least twice so that you make sure that you are not missing anything.

## **Latest Version**

We are constantly reviewing our products. New material is added and old material is revised. Free updates are available for 180 days after the purchase. You should check the products page on the <http://www.chinatag.com> website for an update 3-4 days before the scheduled exam date.

Please tell us what you think of our products. We appreciate both positive and critical comments as your feedback helps us improve future versions. Feedback on specific questions should be send to [feedback@chinatag.com](mailto:feedback@chinatag.com).

Thanks for purchasing our products and look forward to supplying you with all your Certification training needs.

Good studying!

Technical and Support Team  
Chinatag LLC.

## TABLE OF CONTENTS

### List of Tables

### List of Acronyms

### Introduction

## 1. Scaling Internetworks

- 1.1 Characterizing Scalable Internetworks
  - 1.1.1 Reliability and Availability
  - 1.1.2 Responsiveness
  - 1.1.3 Efficiency
  - 1.1.4 Adaptability and Serviceability
  - 1.1.5 Accessibility and Security
- 1.2 Network Congestion
  - 1.2.1 Problems Created by Network Congestion
    - 1.2.1.1 Excessive Traffic
    - 1.2.1.2 Dropped Packets
    - 1.2.1.3 Retransmission of Packets
    - 1.2.1.4 Incomplete Routing Tables
    - 1.2.1.5 Incomplete Server Lists
    - 1.2.1.6 The Spanning-Tree Protocol Breaks
    - 1.2.1.7 Runaway Congestion
  - 1.2.2 Symptoms of Network Congestion
    - 1.2.2.1 Application Time Outs
    - 1.2.2.2. Clients Cannot Connect to Network Resources
    - 1.2.2.3 Network Death Results
- 1.3 Designing Scalable Networks
  - 1.3.1 The Cisco Hierarchical Model
    - 1.3.1.1 Core Layer
    - 1.3.1.2 Distribution Layer
    - 1.3.1.3 Access Layer
- 1.4 Alleviating Congestion
  - 1.4.1 Access Lists
  - 1.4.2 Extended Access Lists
  - 1.4.3 Distribution Lists
  - 1.4.4 Other Solutions to Traffic Control
  - 1.4.5 Prioritization
    - 1.4.5.1 First In, First Out (FIFO)
    - 1.4.5.2 Weighted Fair Queuing (WFQ)
    - 1.4.5.3 Priority Queuing (PQ)

- 1.4.5.4 Custom Queuing
- 1.4.5.5 Class-Based Weighted Fair Queuing (CBWFQ)
- 1.4.5.6 Low-Latency Queuing (LLQ)
- 1.4.6 Null Interface
- 1.4.7 Fast, Autonomous, and Silicon Switching
- 1.4.8 Cisco Express Forwarding (CEF)
- 1.4.9 Enhanced Interior Gateway Routing Protocol (EIGRP)

## 2. Routing

- 2.1 Routing Tables
  - 2.1.1 Static Routing
  - 2.1.2 Dynamic Routing
  - 2.1.3 Routing Updates
  - 2.1.4 Verifying Routing Tables
- 2.2 Routing Protocols
  - 2.2.1 Distance-Vector Routing
  - 2.2.2 Link-State Routing
  - 2.2.3 Classful Routing
  - 2.2.4 Classless Routing
- 2.3 Basic Switching Functions
- 2.4 Convergence
  - 2.4.1 Distance-Vector Routing Convergence
    - 2.4.1.1 RIP and IGRP Convergence
    - 2.4.1.2 EIGRP Convergence
  - 2.4.2 Link-State Convergence
- 2.5 Routing and Switching in a Cisco Router
- 2.6 Testing and Troubleshooting Routes
  - 2.6.1 The **ping** Command
  - 2.6.2 The **traceroute** Command

## 3. IP Addressing

- 3.1 The IP Address
  - 3.1.1 IP Address Classes
  - 3.1.2 Classless Interdomain Routing (CIDR) Notation
  - 3.1.3 Subnetting
  - 3.1.4 Variable-Length Subnet Masks
- 3.2 Summarization
  - 3.2.1 Automatic Summarization
  - 3.2.2 Manual Summarization

- 3.3 Implementing Private IP Addresses
  - 3.3.1 Private IP Addressing
  - 3.3.2 Network Address Translation
- 3.4 The Logical AND Operation
- 3.5 IP Routing
  - 3.5.1 Routing Protocols
  - 3.5.2 The **show ip route** Command
  - 3.5.3 The **clear ip route** Command

## 4. OSPF in a Single Area Network

- 4.1 OSPF Neighbors
  - 4.1.1 Adjacent OSPF Neighbors
- 4.2 The Designated Router (DR) and the Backup Designated Router (BDR)
- 4.3 The OSPF Routing Table
  - 4.3.1 Building the Routing Table on a New OSPF Router
  - 4.3.2 The Topology Database
  - 4.3.3 The Shortest Path First
- 4.4 OSPF Across Nonbroadcast Multiaccess Networks (NBMA)
  - 4.4.1 Physical Interface and Logical Subinterfaces
- 4.5 Problems with OSPF in a Single Area
- 4.6 Configuring OSPF in a Single Area
  - 4.6.1 Configuring OSPF on an Internal Router
    - 4.6.1.1 The **router ospf** Command
    - 4.6.1.2 The **network** Command
  - 4.6.2 Configuring OSPF on the External Router
    - 4.6.2.1 The **interface loopback** Command
    - 4.6.2.2 The **cost** Command
    - 4.6.2.3 The **auto-cost** Command
    - 4.6.2.4 The **priority** Command
  - 4.6.3 Configuring OSPF over an NBMA Topology
    - 4.6.3.1 Configuring OSPF in NBMA Mode
    - 4.6.3.2 Configuring OSPF in Point-to-Multipoint Mode
    - 4.6.3.3 Configuring OSPF in Broadcast Mode
    - 4.6.3.4 Configuring OSPF in Point-to-Point Mode on a Frame Relay Subinterface
- 4.7 Verifying the OSPF Configuration on a Single Router

## 5. OSPF in a Multiple Area Network

- 5.1 Different Router Types
- 5.2 The Link-State Advertisements
- 5.3 OSPF Path Selection Between Areas
  - 5.3.1 The Path to Another Area
  - 5.3.2 The Path to Another AS
- 5.4 Different Types of Areas
- 5.5 Design Considerations in Multiple Area OSPF
  - 5.5.1 Cisco Design Guidelines
  - 5.5.2 Summarization
  - 5.5.3 The Virtual Link
  - 5.5.4 OSPF over an NBMA Network
- 5.6 Configuring OSPF in a Multiple Area Network
  - 5.6.1 The **network** Command
  - 5.6.2 The **area range** Command for an ABR
  - 5.6.3 The **summary-address** Command for an ASBR
  - 5.6.4 The **area** Command
  - 5.6.5 Configuring a Virtual Link
- 5.7 Verifying the OSPF Configuration a Multiple Area Network

## **6. EIGRP in Enterprise Networks**

- 6.1 Operation of EIGRP
  - 6.1.1 The Neighbor Table
  - 6.1.2 The Topology Table
  - 6.1.3 EIGRP Metrics
- 6.2 Updating the Routing Table
  - 6.2.1 Updating the Routing Table in Passive Mode
  - 6.2.2 Updating the Routing Table in Active Mode
  - 6.2.3 Adding a Network to the Topology Table
  - 6.2.4 Removing a Path or Router from the Topology Table
- 6.3 Scaling EIGRP
- 6.4 Configuring EIGRP
- 6.5 Verifying the EIGRP Operation

## **7. Using BGP-4 to Communicate with Other Autonomous Systems**

- 7.1 BGP-4 Overview
  - 7.1.1 The BGP-4 Operation

- 7.1.2 Types of BGP-4
- 7.1.3 BGP-4 Synchronization
- 7.1.4 BGP-4 Policy-Based Routing
- 7.1.5 BGP-4 Attributes

## 7.2 Basic BGP-4 Configuration Commands

- 7.2.1 Starting the Routing Process
- 7.2.2 Defining the Networks to Be Advertised
- 7.2.3 Identifying Neighbors and Defining Peer Groups
- 7.2.4 Forcing the Next-Hop Address
- 7.2.5 Disabling Synchronization
- 7.2.6 Aggregating Routes

## 7.3 Effecting BGP-4 Configuration Changes

## 7.4 Verifying the Basic BGP-4 Configuration

## 7.5 Advanced BGP-4 Configuration

- 7.5.1 Configuring Route Reflectors
- 7.5.2 Controlling BGP-4 Traffic
- 7.5.3 Redundant Connections into the Internet
- 7.5.4 Determining the BGP-4 Path by Configuring the Attributes

## 7.6 Verifying the Advanced BGP-4 Configuration

# 8. Using Integrated IS-IS in Connectionless Networks

## 8.1. IS-IS Overview

- 8.1.1 The OSI Connectionless Network Service (CLNS)
- 8.1.2 Integrated IS-IS

## 8.2 IS-IS Operations

- 8.2.1 IS-IS Data-Flow Diagram
- 8.2.2 Adjacency Building
- 8.2.3 The Link-State Database and Reliable Flooding
- 8.2.4 DIS and Pseudonodes
- 8.2.5 IS-IS Metrics

## 8.3 IS-IS Routing

- 8.3.1 IP Routing with IS-IS

## 8.4 Security

## 8.5 Configuring Integrated IS-IS

- 8.5.1 Enabling IS-IS and Assigning Areas
- 8.5.2 Enabling IP Routing for an Area on an Interface
- 8.5.3 Configuring Optional Interface Parameters
- 8.5.4 Configuring IS-IS Authentication Passwords

8.5.5 Monitoring IS-IS

## **9. Controlling Routing Updates Across the Network**

9.1 Features of Redistribution

9.2 Problems of Configuring Multiple Routing Protocols

9.2.1 Path Selection

9.2.2 Routing Loops

9.2.3 Redistribution and Network Convergence

9.3 Configuring Redistribution

9.4 The Default or Seed Metric

9.4.1 Configuring the Default Metric for OSPF, RIP, EGP or BGP-4

9.4.2 Configuration for EIGRP or IGRP

9.5 Configure the Administrative Distance

9.5.1 Configuring the Administrative Distance in EIGRP

9.5.2 Configuring the Administrative Distance in Other Protocols

9.6 The Passive Interface

9.7 Static Routes

9.8 Controlling Routing Updates with Filtering

9.9 Policy-Based Routing Using Route Maps

9.10 Managing the Redistribution

9.10.1 Trouble shooting Redistribution

9.10.2 Monitoring Policy-Routing Configurations